

**PELICAN™ 8060**  
**FLASHLIGHT UPGRADES**

TECH BULLETIN | 11/04/20

DESIGNED IN

USA































Rev. A

SINCE 1976



Pelican Products, Inc. has upgraded the specs of the Pelican™ 8060 Flashlight.

See below for details.

Previous Generation	New Generation																																																
Part #: 8060-041-110	Part #: 8060-051-110																																																
<table><tr><th>FL1 STANDARD</th><th>HIGH</th><th>MEDIUM</th><th>LOW</th></tr><tr><td></td><td>803 LUMENS</td><td>447 LUMENS</td><td>25 LUMENS</td></tr><tr><td></td><td>2h 30min</td><td>4h</td><td>69h</td></tr><tr><td></td><td>359m</td><td>265m</td><td>62m</td></tr><tr><td></td><td>32252cd</td><td>17492cd</td><td>958cd</td></tr><tr><td></td><td colspan="3">IPX4</td></tr></table>	FL1 STANDARD	HIGH	MEDIUM	LOW		803 LUMENS	447 LUMENS	25 LUMENS		2h 30min	4h	69h		359m	265m	62m		32252cd	17492cd	958cd		IPX4			<table><tr><th>FL1 STANDARD</th><th>HIGH</th><th>MEDIUM</th><th>LOW</th></tr><tr><td></td><td>1072 LUMENS</td><td>551 LUMENS</td><td>29 LUMENS</td></tr><tr><td></td><td>3h 45min</td><td>4h 15min</td><td>60h</td></tr><tr><td></td><td>376m</td><td>265m</td><td>60m</td></tr><tr><td></td><td>35300cd</td><td>17520cd</td><td>889cd</td></tr><tr><td></td><td colspan="3">IPX6</td></tr></table>	FL1 STANDARD	HIGH	MEDIUM	LOW		1072 LUMENS	551 LUMENS	29 LUMENS		3h 45min	4h 15min	60h		376m	265m	60m		35300cd	17520cd	889cd		IPX6		
FL1 STANDARD	HIGH	MEDIUM	LOW																																														
	803 LUMENS	447 LUMENS	25 LUMENS																																														
	2h 30min	4h	69h																																														
	359m	265m	62m																																														
	32252cd	17492cd	958cd																																														
	IPX4																																																
FL1 STANDARD	HIGH	MEDIUM	LOW																																														
	1072 LUMENS	551 LUMENS	29 LUMENS																																														
	3h 45min	4h 15min	60h																																														
	376m	265m	60m																																														
	35300cd	17520cd	889cd																																														
	IPX6																																																



Pelican Products, Inc.

23215 Early Avenue, Torrance, CA 90505

Tel: (310) 326-4700 • Toll Free (800) 473-5422

PELICAN.COM

All trademarks are registered and/or unregistered trademarks of Pelican Products, Inc., its subsidiaries and/or affiliates.

**GUARANTEED FOR LIFE**  
 SEE [PELICAN.COM/WARRANTY](http://PELICAN.COM/WARRANTY) FOR FULL DETAILS